



The Strong Ones



Dynamic 745 Series

Ultrasonic Welding Machine 35 kHz

The ultrasonic welding machine Dynamic 745 Series is suitable for welding operations of thermoplastic parts from small to medium size.





- Can be calibrated
- Highest repeatability with process optimized force profiling
- Suitable for validation
- Designed for the assembly into special purpose machines
- High process reliability

Specification Dynamic 745_{Series}

Operating frequency:	35 kHz	
Safety:	This ultrasonic welding machine conforms to CE standards and thus corresponds to the European safety requirements	
Switches:	Two-hand start. EMERGENCY STOP is at the front	
Drive type:	Pneumatic double acting cylinder Ø 40 mm	
Drive energy:	Compressed air supply:	7 bar maximum 6 bar nominal Maximum consumption at 6 bar: approx. 2.5 lt.n/stroke
Maximum force:	745 N at 6 bar compressed air	
Maximum stroke:	100 mm	
Weight:	41 kg without generator	
Throat depth:	170 mm from the centre line of the horn to the column	
Height adjustment:	180 mm using height adjusting mechanism	
Generator:	ACU35-900	

Additional technical information available on request.



TECHSPAN GROUP

Australia: Ph: 1-800 148 791 www.rincoultrasonics.com.au

New Zealand: Ph: ++64 9 827 6567 www.rincoultrasonics.co.nz