



The Strong Ones



Sound enclosures SSK

Sound Enclosures 20 kHz

The Sound Enclosures SSK-F and SSK-G are suitable for the quieter operation of 20 kHz ultrasonic welding machines.





- High sound absorption
- Base unit for optimum working height optionally available
- Actuation using two-hand start, in accordance with CE standards
- SUVA sound measuring report confirms compliance with the relevant EU-directive

Specification Sound Enclosure

The Sound Enclosures SSK-F and SSK-G are normally delivered complete assembled together with the relevant ultrasonic welding machine. Retrofitting is also possible.

In order to gain an optimum working height, a height adjustable base unit is available for the Sound Enclosures SSK-F and SSK-G (100 mm)

Variants:	SSK-G for the ultrasonic welding machine Dynamic 3000 Series SSK-F for the ultrasonic welding machine MP202 and MP2022
Operating frequency:	20 kHz
Safety:	These Sound Enclosures conform to CE standards and thus correspond to the European safety requirements
Dimensions WxHxD:	760x1700x800 mm
Weight:	120 kg
Options:	Base Unit

Additional technical information available on request.



TECHSPANGROUP

Australia: Ph: 1-800 148 791 www.rincoultrasonics.com.au

New Zealand: Ph: ++64 9 827 6567 www.rincoultrasonics.co.nz